

## NAME

CyclesDetection

## SYNOPSIS

```
use Graph::CyclesDetection;  
use Graph::CyclesDetection qw(:all);
```

## DESCRIPTION

CyclesDetection class provides the following methods:

new, Copy, DetectCycles, DetectCyclesUsingCollapsingPathGraphMethodology, GetAllCyclicPaths, GetIndependentCyclicPaths, StringifyCyclesDetection

Cycles in a Graph are detected using collapsing path graph [Ref 31] methodology.

## METHODS

## new

```
$NewCyclesDetection = new Graph::CyclesDetection($Graph);
```

Using specified *Graph*, new method creates a new CyclesDetection object and returns newly created CyclesDetection object.

## Copy

```
$NewCyclesDetection = $CyclesDetection->Copy();
```

Copies *CyclesDetection* and its associated data using Storable::dclone and returns a new CyclesDetection object.

## DetectCycles

```
$CyclesDetection->DetectCycles();
```

Detects all cycles in a graph and returns *CyclesDetection*.

## DetectCyclesUsingCollapsingPathGraphMethodology

```
$CyclesDetection->DetectCyclesUsingCollapsingPathGraphMethodology();
```

Detects all cycles in a graph using collapsing path graph [Ref 31] methodology and returns *CyclesDetection*.

## GetAllCyclicPaths

```
@AllCyclicPaths = $CyclesDetection->GetAllCyclicPaths();  
$NumOfAllCyclicPaths = $CyclesDetection->GetAllCyclicPaths();
```

Returns an array containing references to all cyclic paths identified during cycles detection. In scalar text, number of cycles is returned.

## GetIndependentCyclicPaths

```
@IndependentCyclicPaths = $CyclesDetection->GetAllCyclicPaths();  
$NumOfIndependentCyclicPaths = $CyclesDetection->GetAllCyclicPaths();
```

Returns an array containing references to independent cyclic paths identified during cycles detection. In scalar text, number of cycles is returned.

A set of independent cycles identified during cycles detection doesn't correspond to the basis set of rings or smallest set of smallest rings (SSSR) [ Refs 29-30 ]; instead, set of cycles identified as independent cycles simply correspond to cycles which contain no other cycle as their subcycles and can't be described as a linear combination of smaller cycles. And it also happens to contain all the rings in basis set of rings and SSSR. In other words, it's a superset of a basis set of cycles and SSSR. For example, six four membered cycles are identified for cubane, which is one more than the basis set of cycles.

## StringifyCyclesDetection

```
$String = $CyclesDetection->StringifyCyclesDetection();
```

Returns a string containing information about *CyclesDetection* object.

#### AUTHOR

Manish Sud <msud@san.rr.com>

#### SEE ALSO

Graph.pm, Path.pm, PathGraph.pm

#### COPYRIGHT

Copyright (C) 2024 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.