
NAME

Fingerprints - Fingerprints class

SYNOPSIS

```
use Fingerprints;

use Fingerprints qw(:all);
```

DESCRIPTION

Fingerprints class provides the following methods:

`new`, `FoldFingerprintsByBitDensity`, `FoldFingerprintsBySize`, `GetFingerprintBitsAsBinaryString`, `GetFingerprintBitsAsHexadecimalString`, `GetFingerprintBitsAsRawBinaryString`, `SetFingerprintsBitVector`, `SetMolecule`, `SetSize`, `SetType`

Fingerprints class is used as a base class for various specific fingerprint classes such as `PathLengthFingerprints`. It implements functionality common to fingerprint classes.

Fingerprints class is derived from `ObjectProperty` base class which provides methods not explicitly defined in `Fingerprints` or `ObjectProperty` class using Perl's AUTOLOAD functionality. These methods are generated on-the-fly for a specified object property:

```
Set<PropertyName>(<PropertyValue>);
$PropertyValue = Get<PropertyName>();
Delete<PropertyName>();
```

Fingerprints class uses `FingerprintsBitVector` class to provide bits manipulation functionality.

METHODS

`new`

```
$NewFingerprints = new Fingerprints(%NamesAndValues);
```

Using specified *Fingerprints* property names and values hash, `new` method creates a new object and returns a reference to newly created *Fingerprints* object. By default, following properties are initialized:

```
Molecule = '';
Type = '';
Size = '';
MinSize = '';
MaxSize = '';
FingerprintsBitVector = '';
```

`FoldFingerprintsByBitDensity`

```
$Fingerprints->FoldFingerprintsByBitDensity($BitDensity);
```

Folds fingerprints by recursively reducing its size by half until bit density is greater than or equal to specified *BitDensity* and returns *Fingerprints*

`FoldFingerprintsBySize`

```
$Fingerprints->FoldFingerprintsBySize($Size, [$CheckSizeValue]);
```

Fold fingerprints by recursively reducing its size by half until size is less than or equal to specified *Size* and returns *Fingerprints*. By default, value *Size* is checked to make sure it's:

```
>= MinSize and < Size and IsPowerOfTwo
```

`GetFingerprintBitsAsBinaryString`

```
$BinaryASCIIString =
  $Fingerprints->GetFingerprintBitsAsBinaryString();
```

Returns fingerprints as a binary ASCII string containing 0s and 1s

GetFingerprintBitsAsHexadecimalString

```
$HexadecimalString =  
$Fingerprints->GetFingerprintBitsAsHexadecimalString();
```

Returns fingerprints as a hexadecimal string

GetFingerprintBitsAsRawBinaryString

```
$RawBinaryString =  
$Fingerprints->GetFingerprintBitsAsRawBinaryString();
```

Returns fingerprints as a raw binary string containing packed bit values for each byte

SetFingerprintsBitVector

```
$Fingerprints->SetFingerprintsBitVector($FingerprintsBitVector);
```

Sets *FingerprintsBitVector* object for *Fingerprints* and returns *Fingerprints*

SetMolecule

```
$Fingerprints->SetMolecule($Molecule);
```

Sets *Molecule* object for *Fingerprints* and returns *Fingerprints*

SetSize

```
$Fingerprints->SetSize($Size);
```

Sets *Size* of fingerprints and returns *Fingerprints*

SetType

```
$Fingerprints->SetType($Type);
```

Sets *Type* of fingerprints and returns *Fingerprints*

AUTHOR

Manish Sud <msud@san.rr.com>

SEE ALSO

BitVector.pm, FingerprintsBitVector.pm, PathLengthFingerprints.pm

COPYRIGHT

Copyright (C) 2004-2008 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.