

NAME

ExtractFromPDBFiles.pl - Extract specific data from PDBFile(s)

SYNOPSIS

ExtractFromPDBFiles.pl PDBFile(s)...

ExtractFromPDBFiles.pl [-c, --chains First | All | "ChainID, [ChainID,...]"] [<--CombineChains> yes | no] [-d, --distance number] [--DistanceMode Atom | Hetatm | Residue | XYZ] [--DistanceOrigin "AtomNumber, AtomName" | "HetatmNumber, HetAtmName" | "ResidueName, ResidueNumber, [ChainID]" | "X,Y,Z">] [-h, --help] [-k, --KeepOldRecords yes | no] [-m, --mode Chains | Sequences | Atoms | CAlphas | Distance | NonWater | NonHydrogens] [--ModifyHeader yes | no] [--NonStandardKeep yes | no] [--NonStandardCode character] [-o, --overwrite] [-r, --root rootname] [--SequenceLength number] [--SequenceRecords Atom | SeqRes] [--SequenceIDPrefix FileName | HeaderRecord | Automatic] [--WaterResidueNames Automatic | "ResidueName, [ResidueName,...]"] [-w, --WorkingDir dirname] PDBFile(s)...

DESCRIPTION

Extract specific data from *PDBFile(s)* and generate appropriate PDB or sequence file(s). Multiple PDBFile names are separated by spaces. The valid file extension is *.pdb*. All other file name extensions are ignored during the wild card expansion. All the PDB files in a current directory can be specified either by **.pdb* or the current directory name.

During *Chains* and *Sequences* values of -m, --mode option, all ATOM/HETAM records for chains after the first model in PDB files containing data for multiple models are ignored.

OPTIONS

-c, --chains *First | All | ChainID,[ChainID,...]*

Specify which chains to extract from *PDBFile(s)* during *Chains | Sequences* value of -m, --mode option: first chain, all chains, or a specific list of comma delimited chain IDs. Possible values: *First | All | ChainID,[ChainID,...]*. Default: *First*. Examples:

```
A
A,B
All
```

--CombineChains *yes | no*

Specify whether to concatenate all the chains before generating sequence file(s). Possible values: *yes | no*. Default: *no*

-d, --distance *number*

Specify distance used to extract ATOM and HETATM records during *Distance* value of -m, --mode option. Default: *10.0* angstroms.

--DistanceMode *Atom | Hetatm | Residue | XYZ*

Specify how to extract ATOM and HETATM records from *PDBFile(s)* during *Distance* value of -m, --mode option: extract all the records within a certain distance specified by -d, --distance from an atom or hetroatom record, a residue, or any arbitrary point. Possible values: *Atom | Hetatm | Residue | XYZ*. Default: *XYZ*

During *Residue* value of --distancemode, distance of ATOM/HETATM records is calculated from all the atoms in the residue and the records are selected as long as any atom of the residue lies within the distance specified using -d, --distance option.

--DistanceOrigin "*AtomNumber,AtomName*" | "*HetatmNumber,HetAtmName*" | "*ResidueName,ResidueNumber,[ChainID]*" | "*X,Y,Z*"

This value is --distancemode specific. In general, it identifies a point used to select other ATOM/HETATMS within a specific distance from this point.

For *Atom* value of --distancemode, this option corresponds to an atom specification. Format: *AtomNumber,AtomName*. Example:

```
455,CA
```

For *Hetatm* value of --distancemode, this option corresponds to a hetatm specification. Format: *HetatmNumber,HetAtmName*. Example:

5295 ,C1

For *Residue* value of --distancemode, this option corresponds to a residue specification. Format: *ResidueNumber, ResidueName[,ChainID]*. Example:

```
78 ,MSE
977 ,RET ,A
978 ,RET ,B
```

For *XYZ* value of --distancemode, this option corresponds to a coordinate of an arbitrary point. Format: *X,Y,X*. Example:

```
10.044 ,19.261 , -4.292
```

-h, --help

Print this help message

-k, --KeepOldRecords *yes | no*

Specify whether to transfer old non ATOM and HETATM records from input PDBFile(s) to new PDBFile(s) during *Chains | Atoms | HetAtms | CAlphas | Distance | NonWater | NonHydrogens* value of -m --mode option. By default, except for the HEADER record, all other unnecessary non ATOM/HETATM records are dropped during the generation of new PDB files. Possible values: *yes | no*. Default: *no*.

-m, --mode *Chains | Sequences | Atoms | CAlphas | Distance | NonWater | NonHydrogens*

Specify what to extract from *PDBFile(s)*: *Chains* - retrieve records for specified chains; *Sequences* - generate sequence files for specific chains; *Atoms* - extract atom records; *CAlphas* - extract records for alpha carbon atoms corresponding to amino acids; *Distance* - extract records with in a certain distance from a specific position; *NonWater* - extract records corresponding to residues other than water; *NonHydrogens* - extract non-hydrogen records.

Possible values: *Chains, Sequences Atoms, CAlphas, Distance*. Default value: *NonWater*

During the generation of new PDB files, unnecessary CONECT records are dropped.

For *Chains* mode, data for appropriate chains specified by --c --chains option is extracted from *PDBFile(s)* and placed into new PDB file(s).

For *Sequences* mode, residues names using various sequence related options are extracted for chains specified by --c --chains option from *PDBFile(s)* and FASTA sequence file(s) are generated.

For *Distance* mode, all ATOM and HETATM records with in a distance specified by -d --distance option from a specific atom, residue or a point indicated by --distancemode are extracted and placed into new PDB file(s).

For *NonWater* mode, non water ATOM and HETATM record lines, identified using value of --WaterResidueNames, are extracted and written to new PDB file(s).

For *NonHydrogens* mode, ATOM and HETATOM record lines containing element symbol other than *H* are extracted and written to new PDB file(s).

For all other options, appropriate ATOM and HETATM records are extracted to generate new PDB file(s).

--ModifyHeader *yes | no*

Specify whether to modify HEADER record during the generation of new PDB files for -m, --mode values of *Chains | Atoms | CAlphas | Distance*. Possible values: *yes | no*. Default: *yes*. By default, Classification data is replaced by *Data extracted using MayaChemTools* before writing out HEADER record.

--NonStandardKeep *yes | no*

Specify whether to include and convert non-standard three letter residue codes into a code specified using --nonstandardcode option and include them into sequence file(s) generated during *Sequences* value of -m, --mode option. Possible values: *yes | no*. Default: *yes*

A warning is also printed about the presence of non-standard residues. Any residue other than standard 20 amino acids and 5 nucleic acid is considered non-standard; additionally, HETATM residues in chains also tagged as non-standard.

--NonStandardCode *character*

A single character code to use for non-standard residues. Default: *X*. Possible values: *?, -, or X*

- o, --overwrite
Overwrite existing files
- r, --root *rootname*
New PDB and sequence file name is generated using the root: <Root><Mode>.<Ext>. Default new file name: <PDBFileName>Chain<ChainID>.pdb for *Chains* mode;
<PDBFileName>SequenceChain<ChainID>.fasta for *Sequences* mode;
<PDBFileName>DistanceBy<DistanceMode>.pdb for *Distance* -m, --mode <PDBFileName><Mode>.pdb for *Atoms | CAlphas | NonWater | NonHydrogens* -m, --mode values. This option is ignored for multiple input files.
- SequenceLength *number*
Maximum sequence length per line in sequence file(s). Default: 80
- SequenceRecords *Atom | SeqRes*
Specify which records to use for extracting residue names from *PDBFiles(s)* during *Sequences* value of -m, --mode option: use ATOM records to compile a list of residues in a chain or parse SEQRES record to get a list of residues. Possible values: *Atom | SeqRes*. Default: *Atom*.
- SequenceDPrefix *FileName | HeaderRecord | Automatic*
Specify how to generate a prefix for sequence IDs during *Sequences* value of -m, --mode option: use input file name prefix; retrieve PDB ID from HEADER record; or automatically decide the method for generating the prefix. The chain IDs are also appended to the prefix. Possible values: *FileName | HeaderRecord | Automatic*. Default: *Automatic*
- WaterResidueNames *Automatic | "ResidueName,[ResidueName,...]"*
Identification of water residues during *NonWater* value of -m, --mode option. Possible values: *Automatic | "ResidueName,[ResidueName,...]"*. Default: *Automatic* - corresponds to "HOH,WAT,H2O". You can also specify a different comma delimited list of residue names to use for water.
- w, --WorkingDir *dirname*
Location of working directory. Default: current directory

EXAMPLES

To extract non-water records from Sample2.pdb file and generate Sample2NonWater.pdb file, type:

```
% ExtractFromPDBFiles.pl Sample2.pdb
```

To extract non-water records from Sample2.pdb file using HOH or WAT residue name for water along with all old non-coordinate records and generate Sample2NewNonWater.pdb file, type:

```
% ExtractFromPDBFiles.pl -m NonWater --WaterResidueNames "HOH,WAT"
-KeepOldRecords Yes -r Sample2New -o Sample2.pdb
```

To extract non-hydrogens records from Sample2.pdb file and generate Sample2NonHydrogen.pdb file, type:

```
% ExtractFromPDBFiles.pl -m NonHydrogens Sample2.pdb
```

To extract data for first chain in Sample2.pdb and generate Sample2ChainA.pdb, type file, type:

```
% ExtractFromPDBFiles.pl -m chains -o Sample2.pdb
```

To extract data for both chains in Sample2.pdb and generate Sample2ChainA.pdb and Sample2ChainB.pdb, type:

```
% ExtractFromPDBFiles.pl -m chains -c All -o Sample2.pdb
```

To extract data for alpha carbons in Sample2.pdb and generate Sample2CAlphas.pdb, type:

```
% ExtractFromPDBFiles.pl -m CAlphas -o Sample2.pdb
```

To extract data for all ATOM and HETATM records within 10 angstrom of an atom specified by atom serial number and name "1,N" in Sample2.pdb file and generate Sample2DistanceByAtom.pdb, type:

```
% ExtractFromPDBFiles.pl -m Distance --DistanceMode Atom
  --DistanceOrigin "1,N" -k No --distance 10 -o Sample2.pdb
```

To extract data for all ATOM and HETATM records within 25 angstrom of an arbitrary point "0,0,0" in Sample2.pdb file and generate Sample2DistanceByXYZ.pdb, type:

```
% ExtractFromPDBFiles.pl -m Distance --DistanceMode XYZ
  --DistanceOrigin "0,0,0" -k No --distance 25 -o Sample2.pdb
```

AUTHOR

Manish Sud <msud@san.rr.com>

SEE ALSO

InfoPDBFiles.pl, ModifyPDBFiles.pl

COPYRIGHT

Copyright (C) 2004-2008 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.