
NAME

JoinTextFiles.pl - Join multiple CSV or TSV text files into a single text file

SYNOPSIS

JoinTextFiles.pl TextFiles...

JoinTextFiles.pl [-f, --fast] [-h, --help] [--indelim comma | semicolon] [-l, --label yes | no] [-o, --overwrite] [--outdelim comma | tab | semicolon] [-q, --quote yes | no] [-r, --root rootname] [-w, --workingdir dirname] TextFiles...

DESCRIPTION

Multiple CSV or TSV *TextFiles* are joined to generate a single text file. The file names are separated by spaces. The valid file extensions are *.csv* and *.tsv* for comma/semicolon and tab delimited text files respectively. All other file names are ignored. All the text files in a current directory can be specified by **.csv*, **.tsv*, or the current directory name. The *--indelim* option determines the format of *TextFiles*. Any file which doesn't correspond to the format indicated by *--indelim* option is ignored.

OPTIONS

-f, --fast

In this mode, *--indelim* and *-q --quote* options are ignored. The format of input and output file(s) are assumed to be similar. And the text lines from *TextFiles* are simply transferred to output file without any processing.

-h, --help

Print this help message

--indelim comma | semicolon

Input delimiter for CSV *TextFile(s)*. Possible values: *comma* or *semicolon*. Default value: *comma*. For TSV files, this option is ignored and *tab* is used as a delimiter.

-l, --label yes | no

First line contains column labels. Possible values: *yes* or *no*. Default value: *yes*

-o, --overwrite

Overwrite existing files

--outdelim comma | tab | semicolon

Output text file delimiter. Possible values: *comma*, *tab*, or *semicolon* Default value: *comma*

-q, --quote yes | no

Put quotes around column values in output text file. Possible values: *yes* or *no*. Default value: *yes*

-r, --root rootname

New text file name is generated using the root: *<Root>.<Ext>*. Default file name: *<FirstTextFileName>1To<Count>Joined.<Ext>*. The *csv*, and *tsv* *<Ext>* values are used for *comma/semicolon*, and *tab* delimited text files respectively.

-w, --workingdir dirname

Location of working directory. Default: current directory

EXAMPLES

To join CSV text files, type:

```
% JoinTextFiles.pl -o Sample1.csv Sample2.csv
% JoinTextFiles.pl -o *.csv
```

To join *Sample*.tsv* TSV text files into a *NewSample.tsv* file, type:

```
% JoinTextFiles.pl -o -r NewSample Sample*.tsv
```

AUTHOR

Manish Sud <msud@san.rr.com>

SEE ALSO

MergeTextFiles.pl, ModifyTextFilesFormat.pl, SplitTextFiles.pl

COPYRIGHT

Copyright (C) 2004-2008 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.