

## NAME

InfoNucleicAcids.pl - List properties of nucleic acids

## SYNOPSIS

InfoNucleicAcids.pl NucleicAcidIDs...

InfoNucleicAcids.pl [-h, --help] [-m, --mode NucleicAcidID | NucleicAcidType] [--OutDelim comma | tab | semicolon] [--output STDOUT | File] [--OutputStyle NucleicAcidBlock | NucleicAcidRows] [-o, --overwrite] [--precision number] [--PropertiesMode Categories | Names | All] [-p, --properties CategoryName, [CategoryName,...] | PropertyName, [PropertyName,...]] [--PropertiesListing ByGroup | Alphabetical] [-q, --quote yes | no] [-r, --root rootname] [-w, --WorkingDir dirname] NucleicAcidIDs...

## DESCRIPTION

List nucleic acid properties. Nucleic acids identification supports two types of IDs: code or name. Nucleic acid properties data, in addition to basic information about nucleic acids - code, name, type, chemical formula and molecular weight - include information about exact mass and elemental composition.

## PARAMETERS

NucleicAcidIDs *Code [NucleicAcidName...] | NucleicAcidType [NucleicAcidType...]*

*NucleicAcidIDs* is a space delimited list of values to identify nucleic acids.

For *NucleicAcidID* mode, input value format is: *Code [NucleicAcidName...]*. Default: *A*. Examples:

```
A
dG AMP
Cytidine T UDP dpppA "5'-dATP"
```

For *NucleicAcidType* mode, input value format is: *NucleicAcidType [NucleicAcidType...]*. Default: *A*. Possible values are: *Nucleobase, Nucleoside, Deoxynucleoside, Nucleotide, Deoxynucleotide*. Default: *Nucleoside*.

Examples:

```
Deoxynucleoside
Nucleobase Nucleotide
```

## OPTIONS

-h, --help

Print this help message.

-m, --mode *NucleicAcidID | NucleicAcidType*

Specify nucleic acids for listing properties using one of these methods: nucleic acid code and/or names or nucleic acid type.

Possible values: *NucleicAcidID* or *NucleicAcidType*. Default: *NucleicAcidID*

For *NucleicAcidType*, command line parameters support these type: *Nucleobase, Nucleoside, Deoxynucleoside, Nucleotide, Deoxynucleotide*.

--OutDelim *comma | tab | semicolon*

Output text file delimiter. Possible values: *comma, tab, or semicolon* Default value: *comma*.

--output *STDOUT | File*

List information at STDOUT or write it to a file. Possible values: *STDOUT* or *File*. Default: *STDOUT*. -r, --root option is used to generate output file name.

--OutputStyle *NucleicAcidBlock | NucleicAcidRows*

Specify how to list nucleic acid information: add a new line for each property and present it as a block for each nucleic acid; or include all properties in one line and show it as a single line.

Possible values: *NucleicAcidBlock | NucleicAcidRows*. Default: *NucleicAcidBlock*

An example for *NucleicAcidBlock* output style:

```
Code: Ado
OtherCodes: A
Name: Adenosine
Type: Nucleoside
MolecularFormula: C10H13O4N5
MolecularWeight: 267.2413
... ..
```

An example for *NucleicAcidRows* output style:

```
Code,OtherCodes,Name,Type,MolecularFormula,MolecularWeight
```

-o, --overwrite

Overwrite existing files.

--precision *number*

Precision for listing numerical values. Default: up to 4 decimal places. Valid values: positive integers.

--PropertiesMode *Categories | Names | All*

Specify how property names are specified: use category names; explicit list of property names; or use all available properties. Possible values: *Categories*, *Names*, or *All*. Default: *Categories*.

This option is used in conjunction with -p, --properties option to specify properties of interest.

-p, --properties *CategoryName,[CategoryName,...] | PropertyName,[PropertyName,...]*

This option is --propertiesmode specific. In general, it's a list of comma separated category or property names.

Specify which nucleic acid properties information to list for the nucleic acid IDs specified using command line parameters: list basic information; list all available information; or specify a comma separated list of nucleic acid property names.

Possible values: *Basic | BasicPlus | PropertyName,[PropertyName,...]*. Default: *Basic*.

*Basic* includes: *Code, OtherCodes, Name, Type, MolecularFormula, MolecularWeight*

*BasicPlus* includes: *Code, OtherCodes, Name, Type, MolecularFormula, MolecularWeight, ExactMass, ElementalComposition*

Here is a complete list of available properties: *Code, OtherCodes, BasePair, Name, Type, MolecularFormula, MolecularFormulaAtpH7.5, MolecularWeight, ExactMass, ElementalComposition*.

--PropertiesListing *ByGroup | Alphabetical*

Specify how to list properties for nucleic acids: group by category or an alphabetical by property names. Possible values: *ByGroup* or *Alphabetical*. Default: *ByGroup*

-q, --quote *yes | no*

Put quotes around column values in output text file. Possible values: *yes* or *no*. Default value: *yes*.

-r, --root *rootname*

New text file name is generated using the root: <Root>.<Ext>. File name is only used during *File* value of -o, --output option.

Default file name: *NucleicAcidInfo<mode>.<Ext>*. The csv, and tsv <Ext> values are used for comma/semicolon, and tab delimited text files respectively.

-w, --WorkingDir *dirname*

Location of working directory. Default: current directory.

## EXAMPLES

To list basic properties information for nucleoside A, type:

```
% InfoNucleicAcids.pl
```

To list all available properties information for nucleoside A, type:

```
% InfoNucleicAcids.pl --propertiesmode all A
```

To list all available information for all available nucleic acids, type:

```
% InfoNucleicAcids.pl --propertiesmode All All
```

To list basic properties information for all nucleobases, type:

```
% InfoNucleicAcids.pl -m NucleicAcidType Nucleoside
```

To list basic properties information for all nucleotides and deoxynulceotides, type:

---

```
% InfoNucleicAcids.pl -m NucleicAcidType Nucleotide Deoxynucleotide
```

To list basic properties information for variety of nucleic acids, type:

```
% InfoNucleicAcids.pl A dG AMP Cytidine T UDP "5'-dATP"
```

To list code and molecular weights for nucleosides A, G, C and T, type:

```
% InfoNucleicAcids.pl --PropertiesMode Names --properties  
Code,MolecularWeight A G C T
```

To alphabetically list all the available properties for nucleotides dAMP, dGMP, dCMP, and dTMP in rows instead of nucleic acid blocks with quotes around the values, type:

```
% InfoNucleicAcids.pl --PropertiesMode All --PropertiesListing  
Alphabetical --outputStyle NucleicAcidRows -q yes dAMP dGMP  
dCMP dTMP
```

To alphabetically list all the available properties for all available nucleic acids to a file names NucleicAcidsProperties.csv with quotes around the values, type

```
% InfoNucleicAcids.pl --PropertiesMode All --PropertiesListing  
Alphabetical --output File --OutputStyle NucleicAcidRows -r  
NucleicAcidsProperties -o -q Yes All
```

## AUTHOR

Manish Sud <msud@san.rr.com>

## SEE ALSO

InfoAminoAcids.pl, InfoPeriodicTableElements.pl

## COPYRIGHT

Copyright (C) 2025 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.